# Vue d'ensemble

| FUZE SPOT | FUZE SFX | FUZE PROFILE | FUZE PROFILE CW |
|---|---|---|---|
| SOURCE<br>•305W 6,500K RGBMA 92 CRI LED Engine<br>•30,000 Hour Average LED Life* | SOURCE<br>•300W 6,600K 68+ CRI White LED Engine<br>•CMY Variable Color Mix | SOURCE<br>•305W 6,500K RGBMA 92 CRI LED Engine<br>•30,000 Hour Average LED Life* | SOURCE<br>•380W 6,000K 91 CRI White LED Engine<br>•30,000 Hour Average LED Life* |
| PHOTOMETRIC DATA<br>•10,100+ Total Lumen Output | PHOTOMETRIC DATA<br>•12,000+ Total Lumen Output | PHOTOMETRIC DATA<br>•10,100+ Total Lumen Output | PHOTOMETRIC DATA<br>•11,200 Total Lumen Output |
| EFFECTS<br>•7° - 42° Motorized Zoom<br>•Variable Frost Filter<br>•4 Facet Prism<br>•Motorized Iris<br>•Variable 16-bit Dimming Curve Modes | EFFECTS<br>•4.5° - 38° Motorized Zoom<br>•Remote Focus<br>•Variable Frost Filter<br>•Dual Independent Prisms for Layering<br>•Motorized Iris | EFFECTS<br>•7° - 42° Motorized Zoom<br>•4 Rotating Full Blackout Framing Blades, +/- 45 Index (FUZE PROFILE)<br>•Variable Frost Filter<br>•4 Facet Prism<br>•Motorized Iris<br>•Variable 16-bit Dimming Curve Modes | EFFECTS<br>•9° - 43° Motorized Zoom<br>•4 Rotating Full Blackout Framing Blades, +/- 45 Index<br>•Motorized Iris<br>•Variable 16-bit Dimming Curve Modes |
| GOBOS<br>•2x 6 Rotating / Indexing Interchangeable Glass Gobos (FUZE SPOT)<br>•Animation Wheel | GOBOS<br>•Rotating Gobo Wheel with 8 Interchangeable Glass Gobos<br>•Fixed Gobo Wheel with 10 Gobos | GOBOS<br>•2x 6 Rotating / Indexing Interchangeable Glass Gobos (FUZE SPOT)<br>•1x 6 Rotating / Indexing Glass Gobos, 1x 7 Fixed Glass (FUZE PROFILE)<br>•Animation Wheel | GOBOS<br>•1 Gobo Wheel<br>•7 Rotating / Indexing Interchangeable Glass Gobos |
| CONTROL / CONNECTIONS<br>•4 DMX Channel Modes<br>•16-bit Pan, Tilt, and Dimming Control<br>•DMX Adjustable LED Frequency<br>•DMX, RDM Protocol Support<br>•Locking 5pin XLR In/Out<br>•Locking Power In/Out | CONTROL / CONNECTIONS<br>•31 DMX Channel Modes<br>•16-bit Pan, Tilt, and Dimming Control<br>•DMX, RDM, Art-NET, and sACN Protocol Support<br>•Locking 5pin XLR In/Out<br>•Locking RJ45 Ethernet In/Out | CONTROL / CONNECTIONS<br>•4 DMX Channel Modes<br>•16-bit Pan, Tilt, and Dimming Control<br>•DMX Adjustable LED Frequency<br>•DMX, RDM Protocol Support<br>•Locking 5pin XLR In/Out<br>•Locking Power In/Out | CONTROL / CONNECTIONS<br>•2 DMX Channel Modes<br>•16-bit Pan, Tilt, and Dimming Control<br>•Motorized Focus<br>•DMX, RDM Protocol Support<br>•Locking 5pin XLR In/Out<br>•Locking Power In/Out |
| SIZE / WEIGHT<br>•LxWxH:<br>407 x 256 x 698mm<br>(16.0" x 10.1 x 27.4")<br>•Weight: 21kg (46.3 lbs.) | SIZE / WEIGHT<br>•LxWxH:<br>370 x 230 x 600mm<br>(14.6" x 10.1" x 23.6")<br>•Weight: 19.3kg (46.3 lbs.) | SIZE / WEIGHT<br>•LxWxH:<br>407 x 256 x 698mm<br>(16.0" x 10.1 x 27.4")<br>•Weight: 25kg (55.1 lbs.) | SIZE / WEIGHT<br>•LxWxH:<br>408 x 252 x 698mm<br>(15.9" x 9.9" x 27.4")<br>•Weight: 23.3kg (51.4 lbs.) |

| FUZE MAX SPOT | FUZE MAX PROFILE | FUZE WASH 500 | FUZE WASH FR |
|---|---|---|---|
| SOURCE<br>•800W 6,500K RGBMA LED Engine<br>•30,000 Hour Average LED Life* | SOURCE<br>•800W 6,500K RGBMA LED Engine<br>•30,000 Hour Average LED Life* | SOURCE<br>•480W 6,500K RGBMA 92 CRI LED Engine<br>•30,000 Hour Average LED Life* | SOURCE<br>•480W 6,500K RGBMA 92 CRI LED Engine<br>•30,000 Hour Average LED Life* |
| PHOTOMETRIC DATA<br>•21,000 Total Lumen Output | PHOTOMETRIC DATA<br>•21,000 Total Lumen Output | PHOTOMETRIC DATA<br>•15,000+ Total Lumen Output | PHOTOMETRIC DATA<br>•15,000+ Total Lumen Output |
| EFFECTS<br>•Motorized Zoom<br>•Dual Variable Frost Filter (Medium/ Wash)<br>•4 Facet Round, 4 Facet Linear Prism<br>•Motorized Iris | EFFECTS<br>•Motorized Zoom<br>•4 Rotating Full Blackout Framing Blades, +/- 60° Index<br>•Dual Variable Frost Filter (Medium/ Wash)<br>•4 Facet Round, 4 Facet Linear Prism<br>•Motorized Iris | EFFECTS<br>•9° - 60° Motorized Zoom<br>•Variable Frost Filter<br>•4 Rotating Full Blackout Framing Blades, +/- 45 Index<br>•Motorized Iris<br>•Variable 16-bit Dimming Curve Modes | EFFECTS<br>•9° - 60° Motorized Zoom<br>•Variable Frost Filter<br>•4 Rotating Full Blackout Framing Blades, +/- 45 Index<br>•Motorized Iris<br>•Variable 16-bit Dimming Curve Modes |
| GOBOS<br>•1x 6 Rotating / Indexing Interchangeable Glass Gobos<br>•1x 7 Fixed Interchangeable Glass Gobos<br>•Animation Wheel | GOBOS<br>•1x 6 Rotating / Indexing Interchangeable Glass Gobos<br>•1x 7 Fixed Interchangeable Glass Gobos<br>•Animation Wheel | GOBOS<br>•N/A | GOBOS<br>•N/A |
| CONTROL / CONNECTIONS<br>•4 DMX Channel Modes<br>•16-bit Pan, Tilt, and Dimming Control<br>•DMX Adjustable LED Frequency<br>•DMX, RDM Protocol Support<br>•4 Button Touch Control Panel | CONTROL / CONNECTIONS<br>•4 DMX Channel Modes<br>•16-bit Pan, Tilt, and Dimming Control<br>•DMX Adjustable LED Frequency<br>•DMX, RDM Protocol Support<br>•4 Button Touch Control Panel | CONTROL / CONNECTIONS<br>•4 DMX Channel Modes<br>•16-bit Pan, Tilt, and Dimming Control<br>•DMX Adjustable ED Frequency<br>•Locking RJ45 Ethernet (Artnet, sACN) In/Out | CONTROL / CONNECTIONS<br>•4 DMX Channel Modes<br>•16-bit Pan, Tilt, and Dimming Control<br>•DMX Adjustable LED Frequency<br>•Locking RJ45 Ethernet (Artnet, sACN) In/Out |
| SIZE / WEIGHT<br>•LxWxH:<br>462 x 590 x 719mm<br>(18.19" x 23.2" x 28.3")<br>•Weight: 33.3kg (73.4 lbs.) | SIZE / WEIGHT<br>•LxWxH:<br>462 x 590 x 719mm<br>(18.19" x 23.2" x 28.3")<br>•Weight: 33.3kg (73.4 lbs.) | SIZE / WEIGHT<br>•LxWxH:<br>408 x 256 x 679mm<br>(16.6" x 10.08 x 26.74")<br>•Weight: 28.1 kg (62 lbs.) | SIZE / WEIGHT<br>•LxWxH:<br>408 x 256 x 679mm<br>(16.6" x 10.08 x 26.74")<br>•Weight: 28.1 kg (62 lbs.) |


Elation Professional Europe
Junostraat 2 • 6468 EW Kerkrade • The Netherlands
www.elationlighting.eu


*La durée de vie de la lampe/des LED peut varier en fonction de plusieurs facteurs, notamment, mais sans s'y limiter : Les conditions environnementales, la puissance/tension, Modes d'utilisation (cycles marche-arrêt), contrôle et gradation. Gobos et couleurs. Les spécifications peuvent être modifiées sans préavis.

PROTEUS · ARTISTE · FUZE

BEST AUDIO & LIGHTING
www.bestaudio-lighting.fr





LE MÉLANGE IDÉAL DE LA PERFORMANCE, DES CARACTÉRISTIQUES ET DE LA VALEUR




WORSHIP FACILITIES
NEW PRODUCT
AWARDS
2019



Optional
4-Leaf Motorized Barndoor
for FUZE WASH 500



Optional
Indexable Ovalizer Lens
for FUZE WASH 500




## FULL SPECTRE

Les Fuze Spot et Fuze Profile avec module couteau abritent de puissants moteurs de mélange de couleurs RGBMA à spectre complet qui offrent un IRC élevé et une large gamme de couleurs. Dotés de fonctionnalités complètes et d'une forte performance, les Fuze Spot et Profile sont la combinaison parfaite pour une variété d'applications.

## AUTOMATIQUE ELLIPSOIDAL

Le Fuze Profile CW, doté d'un moteur LED blanc froid, d'un module couteau, de roues de couleur doubles et de gobos, est idéal pour les solutions d'éclairage d'exposition, d'événements corporate et de diffusion TV. Doté d'un moteur LED blanc 380W 91 CRI qui assure une reproduction précise des couleurs, il fournit un éclairage propre et peut être utilisé partout où un appareil entièrement automatisé est nécessaire.

## WASH SUPERIEUR

Le Fuze Wash FR est doté d'un moteur LED RGBMA de 480W offrant un IRC extrêmement élevé et un moteur de couleur à spectre complet, calibré et optimisé pour être utilisé avec les Fuze Profile et Spot. Il est doté d'une conception optique à lentille de Fresnel, offrant un wash doux et uniforme, d'un zoom motorisé et d'un système de couteau interne à fermeture totale pour le contrôle du faisceau et des effets.

## SPOT EFFETS

Conçu comme une tête mobile multifonctionnelle compacte mais puissante pour les spots, les faisceaux et les effets, le Fuze SFX est doté d'un moteur LED blanc de 300 W remarquablement lumineux avec un système de mélange des couleurs CMY. Conçu comme le projecteur d'appoint et d'effets par excellence, offrant des angles de faisceau étroits et une large couverture zoom, il est doté de nombreuses fonctionnalités et d'un nouveau système FX permettant des combinaisons infinies et des looks vraiment spectaculaires.

## CARACTÉRISTIQUES, PERFORMANCES ET VALEUR AU MAXIMUM !

Le Fuze MAX est une tête mobile LED à spectre complet de 21 000 lumens avec moteur LED RGBMA (92 CRI) qui rivalise avec les luminaires à décharge de classe 1000W/1200W. Disponible en versions Spot et Profile framing, le Fuze MAX a été conçu pour des applications d'éclairage de précision telles que le théâtre, la diffusion et les lieux de culte où un spectre chromatique plus large (y compris les blancs dynamiques), un ensemble complet de fonctionnalités et une qualité exceptionnelle sont requis.

## FRESNEL AUTOMATISE

Le Fuze Wash 500™ est un luminaire à tête mobile LED Fresnel à spectre complet conçu pour le théâtre, la télévision, les événements et un large éventail d'autres applications d'éclairage de précision. Il abrite un moteur LED RGBMA de 500W et délivre un puissant rendement allant jusqu'à 17 000 lumens avec un IRC de 92. Il est conçu pour toute application nécessitant un luminaire Fresnel automatisé avec des couleurs exceptionnelles et percutantes, une large plage de zoom et un champ lumineux doux.

Les spécifications peuvent être modifiées sans préavis.