
Product Overview

Artiste Picasso	Artiste Van Gogh	Artiste Mondrian	Artiste Monet	Artiste Rembrandt	Artiste DaVinci
SOURCE •620W, Profile, 6800K Cool White LED Engine • 30,000 Hour Average LED Life*	SOURCE • 380W, Wash, 6500K Bright White LED Engine • 20,000 Hour Average LED Life*	SOURCE • 950W, Profile FX, 6500K Bright White LED Engine • 30,000 Hour Average LED Life*	SOURCE • 950W, Profile, 6500K Bright White LED Engine • 30,000 Hour Average LED Life*	SOURCE • 950W, Wash, 6500K Bright White LED Engine • 30,000 Hour Average LED Life*	SOURCE • 270W, Spot, 7000K Cool White LED engine • 50,000 Hour Average LED Life*
PHOTOMETRIC DATA • 23000 Total Lumen Output • CRI 73+ (87+ with HCRI Filter)	PHOTOMETRIC DATA • 16000 Total Lumen Output • CRI 91	PHOTOMETRIC DATA • 51000 Total Lumen Output • CRI 72+ (84+ with HCRI Filter)	PHOTOMETRIC DATA • 45000 Total Lumen Output • CRI 72+ (84+ with HCRI Filter)	PHOTOMETRIC DATA • 51000 Total Lumen Output • CRI 72+ (82+ with HCRI Filter)	PHOTOMETRIC DATA • 12000 Total Lumen Output • CRI 72+
EFFECTS • 7°-55° Motorized Zoom • 4 Rotating Full Blackout Framing Blades • Full 360° bi-directional Animation Wheel • 4-Facet and Linear Rotating Prisms • 2 Frost Flters • Internal Color, Framing, Prism, and Frost Macros • Motorized Iris with Variable Pulse Effects • Variable 16-bit Dimming Curve Modes • High Speed Electronic Shutter and Strobe • Adjustable LED Refresh Rate Frequency and Gamma	EFFECTS • 7.5°-45° Beam Zoom Angle (PC Lens Included) • 11°-66° Beam Zoom Angle (Fresnel Lens included) • CMY+ CTO Color Mixing • 7 Position Fixed Color Wheel including UV • 4 Independent Barn Doors • Barn Door Index Adjustment • Frost Filter • Remote Focus Adjustment • Electronic Strobe and Variable Dimming Curves • 16-bit Dimming	EFFECTS • 3°-45° Motorized Zoom (226mm / 8 3/4" Front Lens) • 4 Rotating Full Blackout Framing Blades • 360° Continuous Framing Index and Rotation • Full 360° bi-directional Animation Wheel 2 Rotating Prisms • 2 Variable Frost Filters (Light and Wash) • Internal Color, Framing, Prism, and Frost Macros • Motorized Iris with Variable Pulse Effects • Variable 16-bit Dimming Curve Modes	EFFECTS • 6.8°-55° Motorized Zoom (160mm Front Lens) • 4 Rotating Full Blackout Framing Blades • 360° Continuous Framing Index and Rotation • Full 360° bi-directional Animation Wheel • 4-facet and Linear Rotating Prisms • 2 Variable Frost Filters (Light and Wash) • Internal Color, Framing, Prism, and Frost Macros • Motorized Iris with Variable Pulse Effects • Variable 16-bit Dimming Curve Modes	EFFECTS • 8°-50° Motorized Zoom (180mm Front Lens) • 4 Full Blackout Framing Blades • 360° Framing Index - Continuous Framing Rotation • 2 bi-directional Animation Wheels • 2 Variable Frost Filters (Medium, Heavy) • High Speed Iris • Focus Edge Control • Variable 16-bit Dimming Curve Modes • High Speed Electronic Shutter and Strobe • Adjustable LED Refresh Rate Frequency	EFFECTS • 6°-48° Motorized Zoom • 3-Facet and Linear Rotating Prisms and Prism Macros • Full 360° bi-directional Rotating Animation Wheel • Frost Filter Hybrid Wash Effect • Motorized Zoom, Iris, Focus and Auto-Focus • High Speed Electronic Shutter and Strobe • Variable 16-Bit Dimming Curve Modes • Adjustable LED Refresh Rate Frequency and Gamma Brightness
COLOR • Full CMY Color Mixing System • Linear CTO Color Correction • 6 Dichroic Colors including High 87 CRI Filter	COLOR • Full CMY Color Mixing System • Linear CTO Color Correction • 7 Dichroic Colors including UV	COLOR • SpectraColor CMY + RGB Color Mixing Array • Linear CTO Color Correction • 6 Dichroic Colors including High CRI + UV	COLOR • SpectraColor CMY + RGB Color Mixing Array • Linear CTO Color Correction • 6 Dichroic Colors including High CRI + UV	COLOR • SpectraColor CMY + RGB Color Mixing Array • Linear CTO Color Correction • 6 Dichroic Colors including High CRI + UV	COLOR • Full CMY Color Mixing • 7 Dichroic Colors + CTB • Linear CTO Color Correction
GOBOS • 2 Gobo Wheels • 7 Rotating / Indexing Interchangeable Glass • 7 Interchangeable Static-Stamped Metal Gobos	GOBOS • N/A	GOBOS • 2 Gobo Wheels • 12 Rotating / Indexing Interchangeable Glass Gobos	GOBOS • 2 Gobo Wheels • 7 Rotating / Indexing Interchangeable Glass Gobos • 7 Static Interchangeable Glass Gobos	GOBOS • N/A	GOBOS • 2 Gobo Wheels • 6 Rotating / Indexing Interchangeable • 9 Static Interchangeable Metal Gobos
CONTROL / CONNECTIONS • 2 DMX Channel Modes • 16-bit Pan, Tilt, and Dimming Control • Motorized Focus and 5-15m Auto-Focus presets • DMX, RDM, Art-NET, and sACN Protocol Support • Elation's E-FLY™ Internal Wireless DMX Transceiver • 6 Button Touch Panel • Full Color 180° Reversible LCD Menu Display • 8 / 16 Bit Resolution Adjustable Movement • Hibernation Mode • Locking 5pin XLR In/Out • Locking RJ45 Ethernet In/Out • Locking Power In/Out	CONTROL / CONNECTIONS • 2 DMX Channel Modes (22 / 36 Channels) • DMX Adjustable Refresh Rate (900 -25,000 Hz) • 6 Button Touch Panel • Full Color 180° Reversible LCD Menu Display • DMX, RDM, Art-NET, and sACN Protocol Support • Locking 5pin XLR In/Out • Locking RJ45 Ethernet In/Out • Locking Power In/Out	CONTROL / CONNECTIONS • 2 DMX Channel Modes (42 / 68) • 16-bit Pan, Tilt and Dimming Control • Motorized Focus and Auto-Focus Presets • DMX, RDM, Art-NET, and sACN Protocol Support • 6 Button Touch Control Panel • Full Color 180° Reversible LCD Menu Display • Hibernation Mode • Locking 5pin XLR In/Out • Locking RJ45 Ethernet In/Out • Locking Power In	CONTROL / CONNECTIONS • 2 DMX Channel Modes (40 / 67) • 16-bit Pan, Tilt and Dimming Control • Motorized Focus and Auto-FocusPresets • DMX Controllable Variable Fan Modes • DMX, RDM, Art-NET, and sACN Protocol Support • 6 Button Touch Control Panel • Full Color 180° Reversible LCD Menu Display • Hibernation Mode • Locking 5pin XLR In/Out • Locking RJ45 Ethernet In/Out • Locking Power In	CONTROL / CONNECTIONS • 2 DMX Channel Modes • 16-bit Pan, Tilt, and Dimming Control • DMX, RDM, Art-NET, and sACN Protocol Support • 6 Button Touch Control Panel • Full Color 180° Reversible LCD Menu Display • Hibernation Mode • Locking 5pin XLR In/Out • Locking RJ45 Ethernet In/Out • Locking Power In	CONTROL / CONNECTIONS • 3 DMX Channel Modes (40 Total Channels) • 6 Button Touch Control Panel • Full Color 180° Reversible LCD Menu Display • 8 / 16 Bit Resolution Adjustable Movement • Elation's E-FLY™ Internal Wireless DMX Transceiver • DMX, RDM, Art-NET, and sACN Protocol Support • Locking 5pin XLR In/Out • Locking RJ45 Ethernet In/Out • Locking Power In/Out
SIZE / WEIGHT • LxWxH: 457 x 544.5 x 757.5 mm (18.0" x 21.5" x 29.8") • Weight: 38.1 kg (84.0 lbs.)	SIZE / WEIGHT • LxWxH: 399.6 x 447.3 x 669 mm) (15.7" x 17.6" x 26.3") • Weight: 28.5 kg (62.8 lbs.)	SIZE / WEIGHT • LxWxH: 673 x 472 x 870 mm (26.5" x 18.5" x 34.2") • Weight: 47.5 kg (104.7 lbs.)	SIZE / WEIGHT • LxWxH: 471.1 x 583.4 x 800.4 mm (18.6" x 22.9" x 31.5" in) • Weight: 42.6 kg (94.0 lbs.)	SIZE / WEIGHT • LxWxH: 471 x 333 x 805 mm (18.5" x 31.1" x 31.7" in) • Height (optional PC Lens) 793 mm (31.2") • Weight: 43 kg (94.7lbs.)	SIZE / WEIGHT • LxWxH: : 416 x 284 x 645 mm (16.4" x 11.2" x 25.4" in) • Weight: 25.4 kg (56.0 lbs.)



Elation Professional Europe
Junostraat 2 • 6468 EW Kerkrade • The Netherlands
www.elationlighting.eu



*Lamp/ LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming. Gobos & Colors. Specifications subject to change without notice.



BEST AUDIO & LIGHTING
www.bestaudio-lighting.fr





Avec de plus grandes possibilités vient une plus grande liberté de création et avec la série Artiste, la porte artistique est grande ouverte. Les concepteurs du monde entier découvrent que ces luminaires de qualité théâtrale, plusieurs fois récompensés, sont aussi créatifs que les icônes artistiques dont ils portent le nom. Artiste a établi une nouvelle référence pour l'expression créative dans les lyres LED automatisées.

DESIGN CREATIF

Conçus pour faciliter la tâche de conception tout en permettant aux concepteurs de créer des œuvres d'art vraiment uniques, ces luminaires d'inspiration de qualité théâtrale (spot, profil et wash) avec moteurs à LED blanches offrent une palette complète pour le concepteur créatif dans un design économe en énergie.

COLORIMETRIE

Le choix de la couleur étant peut-être l'élément central de la création d'une ambiance, ces luminaires innovants offrent des systèmes de mélange de couleurs CMY ou CMYRGB SpectraColor capables de produire un spectre complet de nuances allant des pastels délicats aux saturations riches. La correction linéaire des couleurs CTO a été incluse pour un contrôle plus raffiné de la température des couleurs et une gamme de couleurs plus étendue. Les conceptions optiques de pointe s'associent à des moteurs de LED hautement efficaces pour produire une qualité de lumière constante et des projections globalement supérieures.

CADRAGE SANS LIMITE

La possibilité de manipuler la forme du faisceau est vitale dans l'éclairage professionnel, notamment dans les environnements théâtraux. Un système d'indexation illimitée et de rotation continue permet aux utilisateurs non seulement d'affiner la forme du faisceau et de l'encadrer autour des objets à mettre en valeur, mais aussi de réaliser des transitions créatives, des projections, des révélations et des effets aériens lorsqu'il est utilisé en combinaison avec les 4 couteaux à occultation totale.

CARACTERISTIQUES

Les modèles Mondrian, Monet et Rembrandt sont dotés de packs d'effets de pointe pour compléter n'importe quel décor de spectacle.
Les modèles DaVinci et Picasso sont dotés de nombreuses fonctionnalités et options de conception graphique telles que le zoom, les gobos, l'animation, l'ajout de couleurs et de prismes, tandis que le luminaire wash Van Gogh est le partenaire idéal avec ses options de lentilles Fresnel ou PC.

SpectraColor

Grâce au mélange de couleurs SpectraColor exclusif Elation, les Artiste Monet, Mondrian et Rembrandt sont capables de projeter certaines des couleurs les plus magnifiques jamais produites par un luminaire LED automatisé. SpectraColor combine la norme industrielle CMY avec des drapeaux RVB complémentaires pour la capacité de passer des pastels doux aux couleurs primaires saturées profondes. Avec l'ajout d'un CTO variable, ainsi que d'une roue chromatique statique pour couvrir des nuances spécifiques, ces luminaires créatifs peuvent produire les combinaisons de couleurs que les concepteurs d'éclairage exigent.

OPTIQUE SUPERIEUR

Les moteurs lumineux à LED conçus sur mesure pour des systèmes optiques efficaces offrent des performances maximales et une plus grande cohérence dans la projection. Que vous ayez besoin d'un champ uniforme et plat de lumière raffinée, ou d'un hotspot puissant pour de longues distances, la série Artiste a la solution qu'il vous faut. Des projections supplémentaires d'images de gobos en verre et des effets d'animation personnalisés offrent des solutions illimitées de texture et de superposition pour les applications les plus grandes et les plus exigeantes.

Les spécifications peuvent être modifiées sans préavis